


DOCK SOLUTIONS LTD

**UK MANUFACTURED LOADING BAY EQUIPMENT
AND INDUSTRIAL DOORS**

PRODUCT CATALOGUE



Dock Levellers - Scissor Lifts - Industrial Doors - Shelters & Seals
Wheel Guides - Service & Repairs - Load Houses - Fast Action Doors
Control Systems - Bridge Plates - Spares - Traffic Lights - Bumpers

 01594 825200

 sales@docksolutions.co.uk


 www.docksolutions.co.uk

TECHNICAL SPECIFICATION

PRODUCT DETAILS FOR LIFT TABLES AND MOBILE SCISSOR LIFT TABLES

Type	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Motor	Lifting time
	kg	mm	mm	mm	mm	mm	kW	sec.
IL500X	500	860	180	1040	1300	800	0,75	22
IR1000	1000	590	180	770	916	610	1,1	20
IL1000XS	1000	860	180	1040	1300	650	0,75	22
IL1000X	1000	860	180	1040	1300	800	0,75	22
IL1000XB	1000	860	180	1040	1300	1000	0,75	22
IL1000SBS	1000	1050	250	1300	1700	1000	1,1	34
IL1000SB	1000	1050	250	1300	2000	1000	1,1	25
TT1500	1500	1650	300	1950	2500	1300	2,2	35
IL2000	2000	835	200	1035	1300	800	0,75	41
IL2000B	2000	800	230	1030	1300	850	2,2	25
IL2000BBS	2000	1150	250	1400	1700	1500	2,2	-
IL2000SB	2000	1050	250	1300	2000	1000	2,2	25
TB2000	2000	1200	250	1450	1800	800	2,2	21
IL2000SBS	2000	1050	250	1300	1800	1000	2,2	25
TS2000	2000	1500	250	1750	2200	1200	2,2	35
TS2000B	2000	1500	250	1750	2200	1500	2,2	35
IL3000	3000	795	235	1030	1300	800	1,5	38
IL3000B	3000	840	240	1080	1700	1200	2,2	31
IL3000SB	3000	1100	300	1400	2200	1200	2,2	38
IL3000BBS	3000	1170	400	1570	2200	1800	2,2	25
IL3000BB	3000	1170	400	1570	2200	2200	2,2	25
TT3000	3000	1600	350	1950	2500	1300	2,2	-

BESPOKE SIZES ARE AVAILABLE—PLEASE CALL FOR MORE DETAILS

 01594 825200

 sales@docksolutions.co.uk

 www.docksolutions.co.uk

TECHNICAL SPECIFICATION

IL4000B	4000	840	240	1080	1700	1200	2,2	31
IL4000SB	4000	1100	300	1400	2200	1200	2,2	38
IL4000BBS	4000	1170	400	1570	2200	1800	2,2	25
IL4000BB	4000	1170	400	1570	2200	2200	2,2	25
TS4000	4000	1500	350	1850	2200	1200	3,0	60
TS4000B	4000	1500	350	1850	2200	1500	3,0	60
IL5000	5000	2030	600	2630	3000	2000	3,0	60

Double vertical	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Motor	Lifting time
	kg	mm	mm	mm	mm	mm	kW	sec.
IRD500	500	788	162	950	915	610	0,75	20
ILD1000	1000	1475	305	1780	1300	820	2,2	22
ILD2000	2000	1420	360	1780	1300	850	2,2	29
ILD2000B	2000	1420	360	1780	1300	1000	2,2	29
ILD3000	3000	1650	400	2050	1700	1200	2,2	36
ILD4000	4000	1650	400	2050	1700	1200	2,2	36
ILD1000-3	1000	2530	470	3000	1700	1000	2,2	45
ILD2000-3	2000	2440	560	3000	1700	1000	2,2	65
TSD1500	1500	3000	450	3450	2200	1300	2,2	60
ILD400-4	400	3540	600	4140	1700	1000	2,2	40
ILD800-4	800	3504	706	4210	1700	1000	2,2	80

TECHNICAL SPECIFICATION

Double horizontal	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Motor	Lifting time
	kg	mm	mm	mm	mm	mm	kW	sec.
ILH2000	2000	795	205	1000	2500	820	1,1	19
ILH2000SBS	2000	1050	250	1300	3400	1000	2,2	25
ILH3000SB	3000	1050	250	1300	4000	1000	2,2	-
ILH4000B	4000	840	240	1080	3400	1200	2,2	-
ILH4000BBS	4000	1170	400	1570	4400	1800	2,2	-
ILH4000SB	4000	1100	300	1400	4400	1200	2,2	-
TSH4000	4000	1500	350	1850	4400	1200	3,0	-
ILH6000B	6000	840	240	1080	3400	1200	2,2	-
ILH6000SB	6000	1100	300	1400	4400	1200	2,2	-

Low profile	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Motor	Lifting time
	kg	mm	mm	mm	mm	mm	kW	sec.
ICB1000	1000	795	85	880	1450	800	1,1	25
ICB1000B	1000	795	85	880	1450	1140	1,1	25
ICB2000	2000	775	105	880	1600	1000	2,2	15
ICB2500	2500	1570	130	1700	2610	2010	2,2	40
ICBH1000	1000	795	85	880	2900	800	-	-
IU600	600	775	85	860	1450	985	2,2	22
IU1000	1000	795	85	880	1450	1140	1,1	22
IU1500	1500	775	105	880	1600	1180	1,5	15

TECHNICAL SPECIFICATION

Type	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Ah/V	Weight
	kg	mm	mm	mm	mm	mm		kg
I300	300	590	410	1000	950	600	-	-
IZ150	150	490	265	755	700	450	-	41
IZ250	250	580	330	910	830	500	-	78
IZ500	500	565	435	1000	1010	520	-	118
IZ500L	500	820	370	1190	1200	800	-	215
IZ750	750	505	445	950	1010	520	-	120
IZ1000	1000	505	445	950	1010	520	-	137

Double scissor	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width;	Ah/V	Weight
IZD150	150	995	435	1430	830	500	-	90
IZD500	500	1135	440	1575	1010	520	-	168

Electric	Capacity	Stroke	Min. height	Max. height	Platform length	Platform width	Ah/V	Weight
IZ500EL	500	500	450	950	1010	520	75/12	148
IZ750EL	750	500	450	950	1010	520	75/12	154
IZ1000EL	1000	790	430	1220	1200	800	75/12	225
IZD500EL	500	1123	495	1618	1010	520	75/12	198

DOCK SOLUTIONS LTD

**UK MANUFACTURED LOAD BAY EQUIPMENT
AND INDUSTRIAL DOORS**



Dock Solutions Ltd Headquarters

Unit 5
Seymour Business Park
Whimsey Industrial Estate
Cinderford
Gloucestershire
GL14 3JA



sales@docksolutions.co.uk



info@docksolutions.co.uk



01594 825200

Dock Levellers - Scissor Lifts - Industrial Doors - Shelters & Seals
Wheel Guides - Service & Repairs - Load Houses - Fast Action Doors
Control Systems - Bridge Plates - Spares - Traffic Lights - Bumpers